Author Index

Abbas, A. T.	Experimental verification of the autofrettage process for thick-walled tubes	727–736
Abd-AlSamieh, M. F.	Nano-lubricant film formation due to combined elastohydrodynamic and surface force action under isothermal conditions	1019–1029
Adjali, M. H.	A novel tool for the prediction of earth-contact heat transfer: a multi-room simulation	415–422
Ahn, K. Y.	Modelling and analysis of a high-speed circuit breaker mechanism with a spring-actuated cam	663–672
Akdas, D.	Design of a stabilizing controller for a ten-degree-of-freedom bipedal robot using linear quadratic regulator theory	27–43
Alexandrova, N.	Analytical treatment of tube drawing with a mandrel	581–589
Althoefer, K. A.	Theoretical modelling of the self-tapping screw fastening process	135–154
Andrade, F. A.	Gear condition monitoring by a new application of the Kolmogorov–Smirnov test	653–661
Arıcı, M. E.	Analysis of the conjugate effect of wall and flow parameters on pipe flow heat transfer	307–313
Arif, A. F. M.	Gas-assisted laser single-pulse heating: study of thermal stresses	291–306
Arif, A. F. M.	Elastic displacement of the surface due to a laser heating pulse	1271–1282
Badi, M. N. M.	Gear condition monitoring by a new application of the Kolmogorov–Smirnov test	653–661
Bailey, C.	A non-Newtonian computational fluid dynamics study of the stencil printing process	437–446
Balabani, S.	An experimental and numerical study of the flow past elliptic cylinder arrays	1287–1301
Baragetti, S.	Bending behaviour of double-acting hydraulic actuators	607–619
Barr, G.	Shape factors for beams with misaligned loads	981–993
Bassett, M. D.	Calculation of steady flow pressure loss coefficients for pipe junctions	861–881
Beck, S. B. M.	A comparison of the experimental and computational modelling of the fluidic turn-up vortex amplifier at full and zero swirl conditions	893–903
Benjamin, S. F.	Modelling the flow distribution through automotive catalytic converters	379–383
Bergeles, G.	Numerical simulation of the flow and heat transfer around a cylinder with a pulsating approaching flow at a low Reynolds number	105–119
Bhatikar, S. R.	An artificial neural network module for simulation of the energy storage system of a hybrid electric vehicle	919–932
Bodovillé, G.	Analysis of braking noise and vibration measurements by time–frequency approaches	1381–1400
Brandon, J.	Numerical modelling of defect formation on copper wire surfaces during the wire drawing process	237–246
Brandon, J.	Central burst defect analysis of the wire-drawing process using an accumulated damage parameter	1313–1319
Brandon, J. A.	Distributed-element Preisach model for hysteresis of shape memory alloys	673–682
Brennan, M.	A theoretical and experimental investigation into the vibration response of a flexible rotor and squeeze-film damper assembly	1251–1269
Brennan, M. J.	Optimum tuning of a vibration neutralizer for global vibration control	933–942
Burrows, C. R.	Fault detection and tolerance in synchronous vibration control of rotor–magnetic bearing systems	1401–1416
Burgess, S. C.	Shape factors for beams with misaligned loads	981–993
Burton, R.	Two-dimensional pressure control valve	1031–1039
Butterfield, R.	Dimensional analysis revisited	1365–1375
Castiglia, D.	An experimental and numerical study of the flow past elliptic cylinder arrays	1287–1301
Ceccarelli, M.	Trends in the drawing of mechanisms since the early Middle Ages	269–289
Chang, Y.-J.	Parametric study of the air-side performance of slit fin-and-tube heat exchangers in wet conditions	1111–1121
Charley, J.	Analysis of braking noise and vibration measurements by time–frequency approaches	1381–1400
Chen, C.-H.	Mathematical model of curvature analysis for conjugate surfaces with generalized motion in three dimensions	487–502
Chen, C.-K.	Mathematical model of curvature analysis for conjugate surfaces with generalized motion in three dimensions	487–502
Chen, C.-K.	The surface geometry of rollers with skew rolling steel balls	523–532
Chen, C.-K.	Geometric model of a rolling process for multi-wave tubes	533–545
Chen, C.-K.	Compensating analysis of a double circular-arc helical gear by computerized simulation of meshing	759–771

© IMechE 2001

Chen, F.-C.	On the structural configuration synthesis and geometry of machining centres	641–652
Chen, F.-C.	On the transmission efficiency of a spring-type operating kinematic mechanism for an SF_6 gas-isolated circuit breaker	1239–1249
Chen, W. L.	Effects of misalignment on the transmission characteristics of magnetic couplings	227–235
Chen, X. B.	Mechatronics design for a programmable closed-loop mechanism	365–375
Chen, Y.-C.	Bearing contact of a helical gear pair with involute teeth pinion and modified circular-arc teeth gear	1175–1187
Chen, Z.	A study on the link between coupled plasticity and damage and decohesion for multiscale modelling	259–263
Chen, Z.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158
Chieng, C.-C.	Bubble size and system pressure effects on the phase distribution for two-phase turbulent bubbly flows	121–132
Chiou, S.-T.	Mathematical model of curvature analysis for conjugate surfaces with genealized motion in three dimensions	487–502
Chow, C. L.	Prediction of the forming limit diagram on the basis of the damage criterion under non-proportional loading	405–414
Chow, C. L.	Damage mechanics characterization on the fatigue behaviour of a solder joint material	883–892
Chua, L. P.	The angle-resolved velocity measurements in the impeller passages of a model biocentrifugal pump	547–568
Cigola, M.	Trends in the darwing mechanisms since the early Middle Ages	269–289
Cole, M. O. T.	Fault detection and tolerance in synchronous vibration control of rotor–magnetic bearing systems	1401–1416
Colligon, J. S.	Direct evidence of lubrication in ceramic-on-ceramic total hip replacements	265–268
Craighead, I. A.	Monitoring wood decay in poles by the vibroacoustic response method	905–917
Čudina, M.	Noise generation in vane axial fans due to rotating stall and surge	57–64
Davies, M.	A novel tool for the prediction of earth-contact heat transfer: a multi-room simulation	415–422
Dayou, J.	Optimum tuning of a vibration neutralizer for global vibration control	933–942
Dedouch, K.	Vibration analysis of a circular disc backed by a cylindrical cavity	1303–1311
Degallaix, G.	Analysis of braking noise and vibration measurements by time–frequency approaches	1381–1400
Demenego, A.	New developments in the design and generation of gear drives	747–757
Dissanayake, M. W. M. G.	Dynamic modelling and motion planning for a hybrid legged–wheeled mobile vehicle	7–25
Dooner, D. B.	Function generation utilizing an eight-link mechanism and optimized non-circular gear elements with application to automotive steering	847–857
Dowson, D.	The effect of diametral clearance, motion and loading cycles upon lubrication of metal-on-metal total hip replacements	1–5
Dowson, D.	Direct evidence of lubrication in ceramic-on-ceramic total hip replacements	265–268
Dowson, D.	Transient analysis of isothermal elastohydrodynamic circular point contacts	1159–1173
Drinkwater, B. W.	Measurement of the stiffness of joints in a graphite brick assembly	167–177
Duan, B. Y.	Development of a pilot of an Arecibo-type large spherical radio telescope for the square kilometre array	1321–1329
Duan, Y.	Inverse kinematic analysis for triple-octahedron variable-geometry truss manipulators	247–251
Dukkipati, R. V.	Dynamic Preisach modelling of hysteresis for the piezoceramic actuator system	511–521
Dwyer-Joyce, R. S.	Measurement of the stiffness of joints in a graphite brick assembly	167–177
Earles, S. W. E.	Theoretical modelling of the self-tapping screw fastening process	135–154
Elmer, K. F.	A parsimonious model for the proportional control valve	1357–1363
El-Sobky, H.	Uniaxial crushing of constrained tubes	353–364
Elston, S. J.	Soot temperature and concentration measurements from colour charge coupled device camera images using a three-colour method	1041–1052
Esat, I. I.	Gear condition monitoring by a new application of the Kolmogorov–Smirnov test	653–661
Evangelou, S.	The stability of motorcycles under acceleration and braking	1095–1109
Evans, H. P.	Contact and elastohydrodynamic analysis of worm gears. Part 1: theoretical formulation	817–830
Evans, H. P.	Contact and elastohydrodynamic analysis of worm gears. Part 2: results	831–846
Fan, Q.	New developments in the design and generation of gear drives	747–757
Fang, H. E.	Damage mechanics characterization on the fatigue behaviour of a solder joint material	883–892
Fang, H. E.	A study on the link between coupled plasticity and damage and decohesion for multiscale modelling	259–263
Featherston, C. A.	Distributed-element Preisach model for hysteresis of shape memory alloys	673–682
Feng, N. S.	A non-linear transfer matrix technique for statically indeterminate rotor bearing systems	1343–1355
Fong, Z.-H.	Mathematical model of curvature analysis for conjugate surfaces with generalized motion in three dimensions	487–502

© IMechE 2001

Fox, C. H. J.	The mechanics of an oscillatory rate gyroscope with piezoelectric film actuation and sensing	1211–1221
Fuentes, A.	New developments in the design and generation of gear drives	747–757
Gao, P.	Effect of the pivot assembly on the dynamic behaviour of a head actuator in hard disk drives	461–467
Genin, J.	Static follower problem revisited	1139–1142
Gentle, C. R.	Finite element modelling and load share analysis for involute worm gears with localized tooth contact	805–816
Gentle, C. R.	A parsimonious model for the proportional control valve	1357–1363
Glinski, G. P.	A non-Newtonian computational fluid dynamics study of the stencil printing process	437–446
Gobbi, M.	Analytical formulae for the design of a railway vehicle suspension system	683–698
Goldsmith, A. A. J.	The effect of diametrical clearance, motion and loading cycles upon lubrication of metal-on-metal total hip replacements	1–5
Goldsmith, A. A. J.	Direct evidence of lubrication in ceramic-on-ceramic total hip replacements	265–268
Goodwill, S. R.	Spring damper model of an impact between a tennis ball and racket	1331–1341
Gorman, D. G.	Vibration analysis of a circular disk backed by a cylindrical cavity	1303–1311
Greenwood, J. A.	Contact between a centrally loaded plate and a rigid or elastic base, with application to pivoted pad bearings	623–628
Haake, S. J.	Spring damper model of an impact between a tennis ball and racket	1331–1341
Hahn, E. J.	A non-linear transfer matrix technique for statically indeterminate rotor bearing systems	1343–1355
Haimad, N.	Modelling the flow distribution through automotive catalytic converters	379–383
Hanumanna, D.	Bending fatigue testing of gear teeth under random loading	773–784
Harris, J.	Piecewise linear reliability data analysis with fuzzy sets	1075–1082
Hartley, D. M.	Invariant measures of the closeness to linear dependence of six lines or screws	1145–1151
Hayashi, C.	Design evaluation of multiroll mills for small-diameter wire rolling	77–86
Hidayetoglu, T. K.	Effect of the gear finishing process on bending fatigue crack initiation and propagation in spur gears	785–792
Hill, M.	A theoretical and experimental investigation into the vibration response of a flexible rotor and squeeze-film damper assembly	1251–1269
Hillery, M.	Numerical modelling of defect formation on copper wire surfaces during the wire drawing process	237–246
Hillery, M.	Central burst defect analysis of the wire-drawing process using an accumulated damage parameter	1313–1319
Hills, D. A.	Contact between a pin and a plate with a hole under interference-fit and clearance-fit conditions	629–639
Hills, D. A.	A shrink-fitted peg of finite depth subjected to a tensile load	699–711
Hills, D. A.	A shrink-fitted peg subjected to cyclic loading	713–725
Ho, H. C.	Consideration of manufacturing parameters in the design of grooved globoidal cam indexing mechanisms	95–103
Holmes, R.	A theoretical and experimental investigation into the vibration response of a flexible rotor and squeeze-film damper assembly	1251–1269
Hong, S. S.	Effect of circumferential outlet distortion on the flow characteristics at the impeller exit of a centrifugal pump	1083–1093
Horácek, J.	Vibration analysis of a circular disk backed by a cylindrical cavity	1303-1311
Hou, J. P.	Contact between a pin and a plate with a hole under interference-fit and clearance-fit conditions	629–639
Hsu, M.-H.	On the transmission efficiency of a spring-type operating kinematic mechanism for an SF_6 gas-isolated circuit breaker	1239–1249
Huang, S. M.	Effects of misalignment on the transmission characteristics of magnetic couplings	227–235
Imamura, Y.	Design evaluation of multiroll mills for small-diameter wire rolling	77–86
Jack, L. B.	Support vector machines for detection and characterization of rolling element bearing faults	1065–1074
Jalali-Vahid, D.	Transient analysis of isothermal elastohydrodynamic circular point contacts	1159–1173
Jin, Z. M.	Transient analysis of isothermal elastohydrodynamic circular point contacts	1159–1173
Johnson, V.	An artificial neural network module for simulation of the energy storage system of a hybrid electric vehicle	919–932
Kahangamage, U. P.	Shape factors for beams with misaligned loads	981–993
Kalyon, M.	Exact solution for time exponentially varying pulsed laser heating: convective boundary condition case	591–606
Kalyon, M.	Analytical solution for thermal stresses during the laser pulse heating process	1429–1445

© IMechE 2001

Kang, S. H.	Effect of circumferential outlet distortion on the flow characteristics at the impeller exit of a centrifugal pump	1083–1093
Kashimura, H.	Augmentation of the magnitude of the impulsive wave discharging from a tube	191–199
Kauzlarich, J. J.	Contact between a centrally loaded plate and a rigid or elastic base, with application to pivoted pad bearings	623–628
Kerr, D. R.	Invariant measures of the closeness to linear dependence of six lines or screws	1145–1151
Khorshied, S. A.	Experimental verification of the autofrettage process for thick-walled tubes	727–736
Kikuchi, M.	Coagulation of particles in oil by an a.c. electric field (observation of the coagulation process under various mechanical conditions)	201–209
Kim, H.-D.	Augmentation of the magnitude of the impulsive wave discharging from a tube	191–199
Kim, K.-W.	Two-stage sliding mode controller for vibration suppression of a flexible pointing system	155–166
Kim, S. H.	Modelling and analysis of a high-speed circuit breaker mechanism with a spring-actuated cam	663–672
Kobayashi, Y.	Behaviour of dispersed micro-bubbles in a rotating pipe section	1223–1237
Kong, S.	Contact and elastohydrodynamic analysis of worm gears. Part 1: theoretical formulation	817–830
Kong, S.	Contact and elastohydrodynamic analysis of worm gears. Part 2: results	831–846
Kosse, V.	Design of hammer mills for optimum performance	87–94
Koukouvaos, A.	Analysis of liquid outflow from single-outlet vessels	1189–1210
Kovacevic, R.	Modelling of the laser surface nitriding of Ti–6Al–4V alloy—analysis of heat transfer and residual stresses	315–340
Krishnamurthy, S.	Bending fatigue testing of gear teeth under random loading	773–784
Kubie, J.	Analysis of liquid outflow from single-outlet vessels	1189–1210
Kuboki, T.	Design evaluation of multiroll mills for small-diameter wire rolling	77–86
Kuo, T.-C.	Bubble size and system pressure effects on the phase distribution for two-phase turbulent bubbly flows	121–132
Kuroda, K.	Design evaluation of multiroll mills for small-diameter wire rolling	77–86
Kwon, H. D.	Thermal error measurement and modelling techniques for the five-degree-of-freedom spindle drifts in computer numerically controlled machine tools	469–485
Kwon, K.-S.	Identification of rotating asymmetry in rotating machines by using reverse directional frequency response functions	1053–1063
Labudovic, M.	Modelling of the laser surface nitriding of Ti–6Al–4V alloy—analysis of heat transfer and residual stresses	315–340
Lee, C.-K.	Mathematical model of curvature analysis for conjugate surfaces with generalized motion in three dimensions	487–502
Lee, C.-W.	Identification of rotating asymmetry in rotating machines by using reverse directional frequency response functions	1053–1063
Lee, D. J.	The flow through a plenum–runner system—a comparison of experiment and computation	943–953
Lee, D. J.	Measuring the flow through a model engine inlet system containing a plenum and runners	955–964
Lee, K.	Analysis of the dynamic contact between rotating spur gears by finite element and multi-body dynamics technique	423–435
Lee, K. Y.	Dynamic modelling and motion planning for a hybrid legged–wheeled mobile vehicle	7–25
Lee, S. W.	Thermal error measurement and modelling techniques for the five-degree-of-freedom spindle drifts in computer numerically controlled machine tools	469–485
Lee, W.-S.	Parametric study of the air-side performance of slit fin-and-tube heat exchangers in wet conditions	1111–1121
Leo, H. L.	The angle-resolved velocity measurements in the impeller passages of a model biocentrifugal pump	547–568
Li, D.	Fuzzy control of a three-tank system	505–510
Liang, X.	An energy recovery system for a hydraulic crane	737–744
Liew, A.	A non-linear transfer matrix technique for statically indeterminate rotor bearing systems	1343–1355
Limebeer, D. J. N.	The stability of motorcycles under acceleration and braking	1095–1109
Lin, R.	Effect of the pivot assembly on the dynamic behaviour of a head actuator in hard disk drives	461–467
Litvin, F. L.	New developments in the design and generation of gear drives	747–757
Liu, A.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158
Liu, Y.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158
Loong, V. K.-S.	Design of a load cell for measuring ultrasonic percussive drilling forces	965–972
McKay, S.	The development of a three-dimensional imaging system and its application in fluid mechanics	1459–1463

© IMechE 2001

Mahajan, R. L.	An artificial neural network module for simulation of the energy storage system of a hybrid electric vehicle	919–932
Mastinu, G. R. M.	Analytical formulae for the design of a railway vehicle suspension system	683–698
Mathew, J.	Design of hammer mills for optimum performance	87–94
Matsubara, D.	Behaviour of dispersed micro-bubbles in a rotating pipe section	1223–1237
Matsubara, D.	Flow characteristics and micro-bubble behaviour in a rotating pipe section with an abrupt enlargement	1447–1457
Medrano-Cerda, G. A.	Design of a stabilizing controller for a ten-degree-of-freedom bipedal robot using linear quadratic regulator theory	27–43
Mohanty, A. R.	Vibration analysis of a misaligned rotor–coupling–bearing system passing through the critical speed	1417–1428
Morrish, L.	An experimental method to measure gear tooth stiffness throughout and beyond the path of contact	793–803
Mottershead, J. E.	Optimal suppression of parametric vibration in discs under rotating frictional loads	65–75
Mugadu, A.	A shrink-fitted peg of finite depth subjected to a tensile load	699–711
Mugadu, A.	A shrink-fitted peg subjected to cyclic loading	713–725
Munro, R. G.	An experimental method to measure gear tooth stiffness throughout and beyond the path of contact	793–803
Naganathan, N. G.	Dynamic Preisach modelling of hysteresis for the piezoceramic actuator system	511–521
Nan, R. D.	Development of a pilot of an Arecibo-type large spherical radio telescope for the square kilometre array	1321–1329
Nandi, A. K.	Support vector machines for detection and characterization of rolling element bearing faults	1065–1074
Narayanan, S.	Bending fatigue testing of gear teeth under random loading	773–784
Ng, S. P.	Spring constants of filament-wound composite circular rings	211–226
Ngemoh, F. A.	Theoretical modelling of the self-tapping screw fastening process	135–154
Nishimura, N.	Coagulation of particles in oil by an a.c. electric field (observation of the coagulation process under various mechanical conditions)	201–209
Nobili, A.	Exact deflection expressions for a thin solid circular plate loaded by periphery couples	341–351
Ouyang, H.	Optimal suppression of parametric vibration in discs under rotating frictional loads	65–75
Pace, G. D.	Analytical formulae for the design of a railway vehicle suspension system	683–698
Pahk, H. J.	Thermal error measurement and modelling techniques for the five-degree-of-freedom spindle drifts in computer numerically controlled machine tools	469–485
Palmer, D.	An experimental method to measure gear tooth stiffness throughout and beyond the path of contact	793–803
Papadakis, G.	Numerical simulation of the flow and heat transfer around a cylinder with a pulsating approaching flow at a low Reynolds number	105–119
Papadakis, G.	An experimental and numerical study of the flow past elliptic cylinder arrays	1287–1301
Park, J.-H.	Two-stage sliding mode controller for vibration suppression of a flexible pointing system	155–166
Payne, J. F. B.	Measurement of the stiffness of joints in a graphite brick assembly	167–177
Pearson, R. J.	Calculation of steady flow pressure loss coefficients for pipe junctions	861–881
Peng, B.	Development of a pilot of an Arecibo-type large spherical radio telescope for the square kilometre array	1321–1329
Pericleous, K. A.	A non-Newtonian computational fluid dynamics study of the stencil printing process	437–446
Pham, D. T.	Fuzzy control of a three-tank system	505–510
Phelan, P.	Numerical modelling of defect formation on copper wire surfaces during the wire drawing process	237–246
Phelan, P.	Central burst defect analysis of the wire-drawing process using an accumulated damage parameter	1313–1319
Pierson, S.	The flow through a plenum–runner system—a comparison of experiment and computation	943–953
Pierson, S.	Measuring the flow through a model engine inlet system containing a plenum and runners	955–964
Prabhakar, S.	Vibration analysis of a misaligned rotor–coupling–bearing system passing through the critical speed	1417–1428
Pritchard, D.	Damping characteristics of particle dampers—some preliminary results	253–257
Qu, L.	A new practical modal method for rotor balancing	179–189
Ragab, A. R.	Experimental verification of the autofrettage process for thick-walled tubes	727–736
Raghunathan, R. S.	Augmentation of the magnitude of the impulsive wave discharging from a tube	191–199
Rahnejat, H.	Nano-lubricant film formation due to combined elastohydrodynamic and surface force action under isothermal conditions	1019–1029
Rahnejat, H.	Transient analysis of isothermal elastohydrodynamic circular point contacts	1159–1173
Rao, S. S.	Minimization of transmission error in helical gears	447–459

© IMechE 2001

Redstall, M.	Monitoring wood decay in poles by the vibroacoustic response method	905–917
Reese, J. M.	Vibration analysis of a circular disc backed by a cylindrical cavity	1303–1311
Reid, S. R.	Spring constants of filament-wound composite circular rings	211–226
Richardson, S. H.	The flow through a plenum–runner system—a comparison of experiment and computation	943–953
Richardson, S. H.	Measuring the flow through a model engine inlet system containing a plenum and runners	955–964
Roberts, C. A.	Modelling the flow distribution through automotive catalytic converters	379–383
Robinson, A. M.	Measurement of the stiffness of joints in a graphite brick assembly	167–177
Royle, C. M.	The mechanics of an oscillatory rate gyroscope with piezoelectric film actuation and sensing	1211–1221
Ruan, J.	Two-dimensional pressure control valve	1031–1039
Sahinkaya, M. N.	Fault detection and tolerance in synchronous vibration control of rotor–magnetic bearing systems	1401–1416
Sarkar, S.	Analysis of transitional flow and heat transfer over turbine blades: algebraic versus low-Reynolds-number turbulence model	1003–1018
Sayers, A. T.	On the reverse swing of a cricket ball—modelling and measurements	45–55
Scanlon, T. J.	The development of a three-dimensional imaging system and its application in fluid mechanics	1459–1463
Seireg, A.	Thermal stress effects on the surface durability of gear teeth	973–979
Sekhar, A. S.	Vibration analysis of a misaligned rotor–coupling–bearing system passing through the critical speed	1417–1428
Seneviratne, L. D.	Theoretical modelling of the self-tapping screw fastening process	135–154
Setoguchi, T.	Augmentation of the magnitude of the impulsive wave discharging from a tube	191–199
Sharif, K. J.	Contact and elastohydrodynamic analysis of worm gears. Part 1: theoretical formulation	817–830
Sharif, K. J.	Contact and elastohydrodynamic analysis of worm gears. Part 2: results	831–846
Sharp, R. S.	The stability of motorcycles under acceleration and braking	1095–1109
Shaw, C. T.	The flow through a plenum–runner system—a comparison of experiment and computation	943–953
Shaw, C. T.	Measuring the flow through a model engine inlet system containing a plenum and runners	955–964
Sheu, W.-J.	Parametric study of the air-side performance of slit fin-and-tube heat exchangers in wet conditions	1111–1121
Shuchi, S.	Flow characteristics and micro-bubble behaviour in a rotating pipe section with an abrupt enlargement	1447–1457
Shuja, S. Z.	Gas-assisted laser single-pulse heating: study of thermal stresses	291–306
Shuja, S. Z.	Elastic displacement of the surface due to a laser heating pulse	1271–1282
Siew, C.-C.	A theoretical and experimental investigation into the vibration response of a flexible rotor and squeeze-film damper assembly	1251–1269
Simonini, S.	Soot temperature and concentration measurements from colour charge coupled device camera images using a three-colour method	1041–1052
Singace, A. A.	Uniaxial crushing of constrained tubes	353–364
Smith, J. D.	Accuracy of small encoders for gear transmission errors	995–998
Smith, S. L.	The effect of diametral clearance, motion and loading cycles upon lubrication of metal-on-metal total hip replacements	1–5
Smith, S. L.	Direct evidence of lubrication in ceramic-on-ceramic total hip replacements	265–268
Snidle, R. W.	Contact and elastohydrodynamic analysis of worm gears. Part 1: theroretical formulation	817–830
Shidle, R. W.	Contact and elastohydrodynamic analysis of worm gears. Part 2: results	831–846
Song, C.	Distributed-element Preisach model for hysteresis of shape memory alloys	673–682
Stickland, M. T.	The development of a three-dimensional imaging system and its application in fluid mechanics	1459–1463
Stone, C. R.	Soot temperature and concentration measurements from colour charge coupled device camera images using a three-colour method	1041–1052
Strozzi, A.	Exact deflection expressions for a thin solid circular plate loaded by periphery couples	341–351
Strozzi, A.	Circular solid plate supported along an edge arc and deflected by a central transverse force	389–404
Su, D.	Finite element modelling and load share analysis for involute worm gears with localized tooth contact	805–816
Su, Y. X.	Development of a pilot of an Arecibo-type large spherical radio telescope for the square kilometre array	1321–1329
Sun, G.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158

© IMechE 2001

Sung, C. K.	Effects of misalignment on the transmission characteristics of magnetic couplings	227–235
Tan, H.	Effect of the pivot assembly on the dynamic behaviour of a head actuator in hard disk drives	461–467
Terranova, A.	Bending behaviour of double-acting hydraulic actuators	607–619
Thackery, S.	Monitoring wood decay in poles by the vibroacoustic response method	905–917
Thomas, M. R.	Monitoring wood decay in poles by the vibroacoustic response method	905–917
Tian, G. Y.	Inverse kinematic analysis for triple-octahedron variable-geometry truss manipulators	247–251
Tippetts, J. R.	A comparison of the experimental and computational modelling of the fluidic turn-up vortex amplifier at full and zero swirl conditions	893–903
Tomlinson, G. R.	Damping characteristics of particle dampers—some preliminary results	253–257
Troedsson, I.	A method to determine the dynamic load distribution in a chain drive	569–579
Tsay, C.-B.	Bearing contact of a helical gear pair with involute teeth pinion and modified circular-arc teeth gear	1175–1187
Tsay, D. M.	Consideration of manufacturing parameters in the design of grooved globoidal cam indexing mechanisms	95–103
Tse, P. C.	Spring constants of filament-wound composite circular rings	211–226
Ukrainetz, P.	Two-dimensional pressure control valve	1031–1039
Vaccari, P.	Exact deflection expressions for a thin solid circular plate loaded by periphery couples	341–351
Vaccari, P.	Circular solid plate supported along an edge arc and deflected by a central transverse force	389–404
Valizadeh, R.	Direct evidence of lubrication in ceramic-on-ceramic total hip replacements	265–268
Vecchiato, D.	New developments in the design and generation of gear drives	747–757
Vedmar, L.	A method to determine the dynamic load distribution in a chain drive	569–579
Virvalo, T.	An energy recovery system for a hydraulic crane	737–744
Wang, C.-C.	Parametric study of the air-side performance of slit fin-and-tube heat exchangers in wet conditions	1111-1121
Wang, C.-Y.	Compensating analysis of a double circular-arc helical gear by computerized simulation of meshing	759–771
Wareing, R.	Damping characteristics of particle dampers—some preliminary results	253–257
Wiercigroch, M.	Design of a load cell for measuring ultrasonic percussive drilling forces	965–972
Williams, J. S.	Shape factors for beams with misaligned loads	981–993
Winterbone, D. E.	Calculation of steady flow pressure loss coefficients for pipe junctions	861–881
Wipke, K.	An artificial neural network module for simulation of the energy storage system of a hybrid electric vehicle	919–932
Wojewoda, J.	Design of a load cell for measuring ultrasonic percussive drilling forces	965–972
Wollin, J.	Modelling the flow distribution through automotive catalytic converters	379–383
Woolhouse, R. J.	A comparison of the experimental and computational modelling of the fluidic turn-up vortex amplifier at full and zero swirl conditions	893–903
Wu, J.	Approach to diameter measurement of optical fibres: forward near-axis far-field interference	385–388
Xiao, Z.	Dynamic Preisach modelling of hysteresis for the piezoceramic actuator system	511–521
Xu, B.	A new practical modal method for rotor balancing	179–189
Xu, L.	Effect of the pivot assembly on the dynamic behaviour of a head actuator in hard disk drives	461–467
Xu, L. J.	Inverse kinematic analysis for triple-octahedron variable-geometry truss manipulators	247–251
Xu, P.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158
Xu, Y. M.	Two-dimensional pressure control valve	1031–1039
Yamaguchi, H.	Behaviour of dispersed micro-bubbles in a rotating pipe section	1223–1237
Yamaguchi, H.	Flow characteristics and micro-bubble behaviour in a rotating pipe section with an abrupt enlargement	1447–1457
Yanada, H.	Coagulation of particles in oil by an a.c. electric field (observation of the coagulation process under various mechanical conditions)	201–209
Yang, A.-S.	Bubble size and system pressure effects on the phase distribution for two-phase turbulent bubbly flows	121–132
Yang, F.	Finite element modelling and load share analysis for involute worm gears with localized tooth contact	805–816
Yang, F.	Damage mechanics characterization on the fatigue behaviour of a solder joint material	883–892
Yang, S.-C.	The surface geometry of rollers with skew rolling of steel balls	523–532
Yang, S.-C.	Geometric model of a rolling process for multi-wave tubes	533–545
Yang, S. X.	Inverse kinematic analysis for triple-octahedron variable-geometry truss manipulators	247–251

© IMechE 2001

Yang, X.-J.	Prediction of the forming limit diagram on the basis of the damage criterion under non-proportional loading	405–414
Yau, C. H.	Effects of misalignment on the transmission characteristics of magnetic couplings	227–235
Yianneskis, M.	An experimental and numerical study of the flow past elliptic cylinder arrays	1287–1301
Yilbas, B. S.	Gas-assisted laser single-pulse heating: study of thermal stresses	291–306
Yilbas, B. S.	Exact solution for time exponentially varying pulsed laser heating: convective boundary condition case	591–606
Yilbas, B. S.	Laser short-pulse heating: three-dimensional consideration	1123–1138
Yilbas, B. S.	Elastic displacement of the surface due to a laser heating pulse	1271–1282
Yilbas, B. S.	Analytical solution for thermal stresses during the laser pulse heating process	1429–1445
Yoo, H.-H.	Two-stage sliding mode controller for vibration suppression of a flexible pointing system	155-166
Yoon, K. Y.	Minimization of transmission error in helical gears	447–459
Yu, S. C. M.	The angle-resolved velocity measurements in the impeller passages of a model biocentrifugal pump	547–568
Yu, Y.	Dynamic Preisach modelling of hysteresis for the piezoceramic actuator system	511–521
Zhang, W. J.	Mechatronics design for a programmable closed-loop mechanism	365–375
Zheng, J.	Unique design of the junction between a thick pressure vessel shell and a thinner hemispherical head	1153–1158
Zoras, S.	A novel tool for the prediction of earth-contact heat transfer: a multi-room simulation	415–422

© IMechE 2001